studio

Internorm
Windows – Doors

HF 410 TIMBER-ALUMINIUM-WINDOW

CHARACTERISTICS

Thermal insulation (in W/m²K)
U_w up to 0,64

Sound reduction (in dB)
up to 33 - 46

Security
up to RC1N, RC2

Locking
fully concealed

Installation Depth (in mm)
85

I-tec Glazing



TU Graz
PASSIVHAUSTAUGLICH
NACH RICHTLINIE WA15/2

The uniform combination of interior materials, colours and fittings emphasise your minimalist style and bring exceptional individual pieces to the fore. HF 410 adapts perfectly to your interior design. Different colours and types of timber offer you countless possibilities for your individual interior colour scheme. Made to measure, windows can be combined with fixed glazing to create large surfaces.

TIMBER-ALUMINIUM-WINDOW

HF 410

Cuts

Senkrecht / Vertical



Waagrecht / Horizontal



Stulp / Flying mullion



BM	Bestellmaß / Ordering size	GM	Glasmaß / Glass size
FM G	Flügelmaß Gehflügel / Sash size master sash	RA	Rahmenaußenmaß / Outside frame size
FM S	Flügelmaß Stehflügel / Sash size slave sash	TM	Teilungsmaß / Division size
FOK	Fußbodenoberkante / Finished floor level		

Values

Glass Build Up	GC	Coating	AH	U_g	g	U_f	Psi	U_w	R_w	C	Ctr	Certificate - Thermal Performance	Certificate - Sound
4b/18Ar/4/18Ar/b4	3N2	Low-Carbon iplus	Iso Alu	0,5 0,5	53 53	0,91 0,91	0,036 0,075	0,71 0,81	35 35	-2 -2	-6 -6	✓ ✓	✓ ✓
6b/18Ar/4/16Ar/b4	33U	Low-Carbon iplus	Iso Alu	0,5 0,5	52 52	0,91 0,91	0,039 0,081	0,72 0,82	39 39	-2 -2	-6 -6	✓ ✓	✓ ✓
44b.2(VSG-S)/15Ar/4/12Ar/b44.2(VSG-S)	3FH	Low-Carbon iplus	Iso Alu	0,6 0,6	47 47	0,91 0,91	0,049 0,093	0,81 0,93	46 46	-1 -1	-4 -4	✓ ✓	✓ ✓
4b/18Ar/4/14Ar/b44.2(VSG-S)	39K	Low-Carbon iplus	Iso Alu	0,6 0,6	52 52	0,91 0,91	- -	- -	42 42	-3 -3	-7 -7	× ×	✓ ✓
6b/15Ar/4/14Ar/b44.2(VSG-S)	34P	Low-Carbon iplus	Iso Alu	0,6 0,6	51 51	0,91 0,91	- -	- -	41 41	-2 -2	-6 -6	× ×	✓ ✓

InterHaus Inc
L6K 2E8 Oakville
Speers Road 217
01 888 770 4917

interhaus.ca

TIMBER-ALUMINIUM-WINDOW

HF 410

studio

Internorm takes responsibility for the environment and climate

Internorm's use of low-carbon iplus glass saves 10,000 t of CO_2 eq annually

Glass is an fundamental component in window production. As Europe's leading window brand, we take our responsibility seriously, and incorporate low-carbon iplus insulating glazing in our product range as standard.

In order to reduce greenhouse gas emissions, we analysed the entire low-carbon float glass production chain. This included activities before, during and after the actual manufacturing process, right through to delivery to the customer.

The result is a 4 mm thick, low-carbon float glass with a reduced carbon footprint of 5.5 kg CO_2 eq/m^2 that delivers emission savings of over 45%.

What turns low-carbon iplus glass into thermally insulated glass?

- Use of low-emission raw materials
- Use of highly efficient melting furnaces including electric boosting
- At least 50% recycled content, to conserve valuable raw materials
- Utilisation of renewable energies
- Optimised transport throughout the entire supply chain

InterHaus
PREMIUM WINDOWS AND DOORS

InterHaus Inc
L6K 2E8 Oakville
Speers Road 217
01 888 770 4917

interhaus.ca