


KF 520 UPVC-ALUMINIUM-WINDOW



CHARACTERISTICS



Thermal insulation (in W/m²K)
U_w up to 0,63



Sound reduction (in dB)
up to 33 - 46



Security
up to RC 3



Locking
fully integrated



Installation Depth (in mm)
93

I-tec Glazing

I-tec Secure




A lot of glass, plenty of light, and enhanced security: the KF 520 combines innovative design with technical expertise. The window sash is invisible from the outside thanks to its glass design and is visually indistinguishable from fixed glazing.


This sash also conceals the revolutionary I-tec Secure locking system, which makes it virtually impossible to lever out the window - unrivalled in the industry. Integrated flaps press into the frame profile on all sides when locking, thus offering maximum burglary protection. Also available as a uPVC-aluminium window.

Cuts


Senkrecht / Vertical



Waagrecht / Horizontal



Stulp / Flying mullion



BM Bestellmaß / Ordering size
FM G Flügelmaß Gehflügel / Sash size master sash
FM S Flügelmaß Stehflügel / Sash size slave sash
FOK Fußbodenoberkante / Finished floor level

GM Glasmaß / Glass size
RA Rahmenaußenmaß / Outside frame size
TM Teilungsmaß / Division size

Values

Glass Build Up	GC	Coating	AH	U _g	g	U _f	Psi	U _w	R _w	C	Ctr	Certificate - Thermal Performance	Certificate - Sound
4b/18Ar/4/18Ar/b4	3N2	Low-Carbon iplus	Iso Alu	0,5 0,5	53 53	0,99 0,99	0,033 0,075	0,70 0,81	33 33	-1 -1	-6 -6	✓ ✓	✓ ✓
6b/18Ar/4/16Ar/b4	33U	Low-Carbon iplus	Iso Alu	0,5 0,5	52 52	0,99 0,99	0,033 0,075	0,70 0,81	38 38	-2 -2	-6 -6	✓ ✓	✓ ✓
4b/16Ar/4/15Ar/ b44.2(VSG-S)	34N	Low-Carbon iplus	Iso Alu	0,6 0,6	52 52	0,99 0,99	0,033 0,075	0,78 0,89	41 41	-2 -2	-7 -7	✓ ✓	✓ ✓
44b.2(VSG-S)/15Ar/ 4/12Ar/b44.2(VSG-S)	3FH	Low-Carbon iplus	Iso Alu	0,6 0,6	47 47	0,99 0,99	0,033 0,075	0,78 0,89	46 46	-2 -2	-7 -7	✓ ✓	✓ ✓

Internorm takes responsibility for the environment and climate

Internorm's use of low-carbon iplus glass saves 10,000 t of CO₂ eq annually

Glass is an fundamental component in window production. As Europe's leading window brand, we take our responsibility seriously, and incorporate low-carbon iplus insulating glazing in our product range as standard.

In order to reduce greenhouse gas emissions, we analysed the entire low-carbon float glass production chain. This included activities before, during and after the actual manufacturing process, right through to delivery to the customer.

The result is a 4 mm thick, low-carbon float glass with a reduced carbon footprint of 5.5 kg CO₂ eq/m² that delivers emission savings of over 45%.

What turns low-carbon iplus glass into thermally insulated glass?

- Use of low-emission raw materials
- Use of highly efficient melting furnaces including electric boosting
- At least 50% recycled content, to conserve valuable raw materials
- Utilisation of renewable energies
- Optimised transport throughout the entire supply chain